

SA-STTL (for SIGMA) ELECTRONIC FLASH EF-630

*Operation confirmed by SIGMA(as of August 2021.)

This flash correspond with the fp series, sd Quattro series, SD1/SD1 Merrill, dp Quattro series, DP Merrill series cameras listed below.

	TTL Auto	Autozoom Head	Manual Flash	Multiple Flash	AF Assist light	Red-Eye Reduction Function	FP flash (high-speedsync)	Wireless Flash	Designated Receive function *1	Normal Receive function *1	Rear-curtain Sync flash function	Exposure control function
SD1	STTL	✓	✓	✓	✓	✓	✓	✓	✓	✓ *2	✓	✓ *3
SD1 Merrill	STTL	✓	✓	✓	✓	✓	✓	✓	✓	✓ *2	✓	✓ *3
sd Quattro	STTL	✓	✓	✓	✓	✓	✓	✓ *1	✓	✓	✓	✓ *4
sd Quattro H	STTL	✓	✓	✓	✓	✓	✓	✓ *1	✓	✓	✓	✓ *4
fp	STTL	✓	✓	✓	✓	✓	x	✓ *1	x	✓	✓	✓ *4
fp L	STTL	✓	✓	✓	✓	✓	x	✓ *1	x	✓	✓	✓ *4
DP1 Merrill	STTL	✓	✓	x	x	✓ *5	x	x	x	x	x	✓ *3
DP2 Merrill	STTL	✓	✓	x	x	✓ *5	x	x	x	x	x	✓ *3
DP3 Merrill	STTL	✓	✓	x	x	✓ *5	x	x	x	x	x	✓ *3
dp1 Quattro	STTL	✓	✓	x	x	✓ *5	x	x	x	x	x	✓ *3
dp2 Quattro	STTL	✓	✓	x	x	✓ *5	x	x	x	x	x	✓ *3
dp3 Quattro	STTL	✓	✓	x	x	✓ *5	x	x	x	x	x	✓ *3
dp0 Quattro *6	STTL	✓	✓	x	x	✓ *5	x	x	x	x	x	✓ *3

*1 Using two EF-630s, the flash attached on the camera's hotshoe will be used as the calculate flash.

*2 The built-in flash cannot be used. Please use the manual flash mode to use the external flash attached on the camera hotshoe.

*3 When the exposurecontrol is set both on the camera and flash, the setting of the camera is prioritized.

*4 When the exposurecontrol is set both on the camera and flash, it will be shoot with the totaled value.

*5 This setting is only available on camera.

*6 Please use the built-in wide pannel.